

# EVER-THANE®

# ACCELERATOR

## TECHNICAL DATA SHEET

EVER-THANE® Accelerator is a single component, liquid thickener / accelerator for EVER-THANE® Base Coat and EVER-THANE® White which are part of EVERROOF®'s Cool Roof Systems. This accelerator enhances the moisture curing characteristics that accelerates the cure time and causes the coating to thicken and to cure faster.

### FEATURES & BENEFITS

EVER-THANE® Accelerator allows the coating material to have a faster cure time but still is manageable. When time is on the essence because of incoming weather or small projects, EVER-THANE® Accelerator can save on time and labor cost.

### TYPICAL USES

- EVER-THANE® Accelerator can be used when needed on vertical surfaces, and other areas where quick access is needed.
- Vertical surfaces
- When quick access is necessary
- Creates a caulking compound for plywood joints, cracks, concrete expansion joints and flashings

### DIRECTIONS FOR USE

EVER-THANE® Accelerator may be mixed into EVER-THANE® BASE and EVER-THANE® WHITE. Mix coating material thoroughly then add and mix EVER-THANE® Accelerator into the coating material until a homogeneous mixture and color is obtained or for at least 3 – 5 minutes. The mixing ration of EVER-THANE® Accelerator to coating material is: 1 pint to 5 gallons of coating material (.47 liter to 18.93 liter). The pot life of the resulting thixotropic compound is approximately 20 to 40 minutes at 75°F (24°C) and 50% relative humidity.

### LIMITATIONS:

Excessive EVER-THANE® Accelerator will result in a reduction of the physical properties of the base membrane

- Not UV stable
- Cannot withstand direct wear or abrasion
- After mixing material must be used within 15 – 20 minutes
- Do not dilute under any circumstances

### STORAGE & HANDLING

Review the Safety Data Sheet (SDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

### SAFETY

Review the Safety Data Sheet (SDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.



Please read all information in the general guidelines, technical data sheets, application guide, and safety data sheets (SDS) before applying material. Published technical data and instructions are subject to change without notice. Contact your local EVERROOF® representative or visit our website for current technical data and instructions. **DISCLAIMER:** All guidelines, recommendations, statements and technical data contained herein are based on information and tests that EVERROOF® believes to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. It is the user's responsibility to satisfy himself, by his own information and tests, to determine suitability of the product for his own intended use, application and/or situation and user assumes all risk and liability resulting from his use of the product(s). EVERROOF® does not suggest or guarantee that any hazards listed herein are the only ones that may exist. EVERROOF® shall not be liable to the user or any third party for any injury, loss, damage, or costs directly or indirectly resulting from use of, or inability to use, the product(s). Recommendations or statements, whether verbal or in writing, other than those contained herein shall not be binding upon EVERROOF®, unless in writing and signed by an authorized corporate officer. Technical and application information is provided for the purpose of establishing a general profile of the material and proper application procedures. Test performance results were obtained in a controlled environment and EVERROOF® makes no claim that these tests or any other tests, accurately represent all environments. Not responsible for typographical errors. REV20161102EA