



TGFU.R27681 Roofing Systems

[Page Bottom](#)

Roofing Systems

[See General Information for Roofing Systems](#)

EVERROOF GROUP INTERNATIONAL CORP

R27681

8550 W DESERT INN RD
STE 102-520
LAS VEGAS, NV 89117 USA

MAINTENANCE AND REPAIR SYSTEMS

Class A, B or C

1. **Deck:** C-15/32

Incline: See Note 1

Existing Roof System: — Class A, B or C insulated or uninsulated modified bitumen membrane to maintain existing Class A, B or C Certification covered with:

Primer: — "EVERROOF M100", 0.33-gal/100-ft.².

Seam reinforcement: — "Ever-Thane Fast Flash" applied to seam area 6-in. wide at the rate of 2-lb/gal (24 mils).

Level Coat: — "EVER-THANE BASE" applied at a rate of 11/2-gal./100-ft.².

Base Coat: — "EVER-THANE Base" applied at a rate of 11/2-gal./100-ft.².

Top Coat: — "EVER-THANE WHITE" or "EVER-THANE BRIGHT WHITE" applied at a rate of 11/2-gal./100-ft.².

Note 1: Certification (A, B or C) will be the same as that of the Existing Certified Roofing System with a maximum incline of 31/2 inches (TGFU).

2. **Deck:** C-15/32

Incline: See Note 1

Existing Roof System: — Any Class A, B or C insulated or uninsulated, EPDM, TPO, Hypalon, PVC, TPA, or CPE single ply membrane system, mechanically fastened or fully adhered, to retain existing Certification:

Seam reinforcement: — "Ever-Thane Fast Flash" applied to seam area 6-in. wide at the rate of 11/2-lb/gal (24 mils).

Primer: — "EVERROOF Primer U11" (TPO, Hypalon, PVC, TPA, or CPE) applied at a rate of 0.33-gal/ 100-ft.² or "EVERROOF Primer EPDM" (EPDM), 1/4-gal/100-ft.².

Base Coat: — "EVER-THANE Base" applied at a rate of 11/2-gal./100-ft.².

Top Coat: — "EVER-THANE WHITE" or "EVER-THANE BRIGHT WHITE" applied at a rate of 11/2-gal./100-ft.².

Note 1: Certification (A, B or C) will be the same as that of the Existing Certified Roofing System with a maximum incline of 2-inches (TGFU).

3. **Deck:** C-15/32

Incline: See Note 1

Existing Roof System: — Any Class A, B or C uncoated, insulated or uninsulated, modified bitumen membrane, Type G3 mineral surfaced cap BUR, to retain existing Classification.

Base Coat: — "Ever-Thane Water-Lok Base", 1.5 gal/sq.

Top Coat: — General Coatings Manufacturing Corp. "Ultra-Flex 1800" applied at a rate of 11/2-gal/100-ft.².

Note 1: Classification (A, B or C) will be the same as that of the Classified Roofing System (TGFU) with a maximum incline of 1 inch.

4. **Deck:** C-15/32

Incline: See Note 1

Existing Roof System: — Any Class A, B or C uncoated, insulated or uninsulated, modified bitumen membrane, Type G3 mineral surfaced cap BUR, to retain existing Classification.

Base Coat: — "Ever-Thane Water-Lok Base" applied at a rate of 11/2-gal/100-ft.².

Top Coat: — General Coatings Manufacturing Corp. "Ultra-Guard 5700" applied at a rate of 11/2-gal/100-ft.².

Note 1: Classification (A, B or C) will be the same as that of the Classified Roofing System (TGFU) with a maximum incline of 1 inch.

5. **Deck:** C-15/32

Incline: See Note 1

Existing Roof System: — Any Class A, B or C uncoated, insulated or uninsulated, modified bitumen membrane, Type G3 mineral surfaced cap BUR, EPDM, TPO, Hypalon, TPA, or CPE single ply membrane system, mechanically fastened or fully adhered, to retain existing Classification.

Base Coat: — "Ever-Crylic Base Coat" applied at a rate of 11/2-gal./100-ft.².

Top Coat: — "Ever-Crylic Top Coat" applied at a rate of 11/2-gal./100-ft.².

Note 1: Classification (A, B or C) will be the same as that of the Classified Roofing System (TGFU) with a maximum incline of 1 inch.

6. **Deck:** C-15/32**Incline:** See Note 1**Existing Roof System:** — Any Class A, B or C uncoated, insulated or uninsulated, PVC single ply membrane system, mechanically fastened or fully adhered, to retain existing Classification.**Base Coat:** — "Ever-Crylic Base Coat" applied at a rate of 11/2-gal./100-ft.².**Top Coat:** — "Ever-Crylic Top Coat" applied at a rate of 11/2-gal./100-ft.².**Note 1:** Classification (A, B or C) will be the same as that of the Classified Roofing System (TGFU) with a maximum incline of 1/2 inch.7. **Deck:** C-15/32**Incline:** See Note 1**Existing Roof System:** — Any Class A, B or C uncoated, insulated or uninsulated, modified bitumen membrane, Type G3 mineral surfaced cap BUR, EPDM, TPO, Hypalon, PVC, TPA, or CPE single ply membrane system, mechanically fastened or fully adhered, to retain existing Classification.**Surfacing:** — "Ever-Silic HS" applied at a rate of 11/2-gal./100-ft.².**Note 1:** Classification (A, B or C) and maximum incline will be the same as that of the Classified Roofing System (TGFU).8. **Deck:** C-15/32**Incline:** See Note 1**Existing Roof System:** — Any Class A, B or C uncoated, insulated or uninsulated, modified bitumen membrane, Type G3 mineral surfaced cap BUR, EPDM, TPO, Hypalon, PVC, TPA, or CPE single ply membrane system, mechanically fastened or fully adhered, to retain existing Classification.**Base Coat:** — Everroof Group International Corp. "EVER-THANE Base" applied at a rate of 11/2-gal./100-ft.².**Top Coat:** — "Ever-Silic HS" applied at a rate of 11/2-gal./100-ft.².**Note 1:** Classification (A, B or C) and maximum incline will be the same as that of the Classified Roofing System (TGFU).9. **Deck:** C-15/32**Incline:** See Note 1**Existing Roof System:** — Any Class A, B or C uncoated, insulated or uninsulated, modified bitumen membrane, Type G3 mineral surfaced cap BUR, to retain existing Classification.**Base Coat:** — Everroof Group International Corp. "Ever-Thane Water-Lok Base", 1.5-gal/sq.**Top Coat:** — "Ever-Crylic Top Coat" applied at a rate of 11/2-gal./100-ft.².**Note 1:** Classification (A, B or C) will be the same as that of the Classified Roofing System (TGFU) with a maximum incline of 1 inch.10. **Deck:** C-15/32**Incline:** See Note 1**Existing Roof System:** — Any Class A, B or C uncoated, insulated or uninsulated, modified bitumen membrane, Type G3 mineral surfaced cap BUR, to retain existing Classification.**Base Coat:** — Everroof Group International Corp. "Ever-Thane Water-Lok Base" applied at a rate of 11/2-gal./100-ft.².**Top Coat:** — "Ever-Silic HS" applied at a rate of 11/2-gal./100-ft.².**Note 1:** Classification (A, B or C) will be the same as that of the Classified Roofing System (TGFU) with a maximum incline of 1 inch.**FLUID APPLIED COATING SYSTEMS****Class A**1. **Deck:** NC**Incline:** Unlimited**Base Coat:** — EVER-THANE Base" applied at a rate of 11/2-gal./100-ft.².**Top Coat:** — "EVER-THANE WHITE" or "EVER-THANE BRIGHT WHITE" applied at a rate of 11/2-gal./100-ft.².**SPRAY APPLIED FOAM AND COATING SYSTEMS****Class A**1. **Deck:** NC**Incline:** 1/2**Foam:** — General Coatings Manufacturing Corp. "Ultra-Thane 230", 1-in. minimum.**Base Coat:** — "EVER-THANE Base" applied at a rate of 11/2-gal./100-ft.².**Top Coat:** — "EVER-THANE WHITE" or "EVER-THANE BRIGHT WHITE" applied at a rate of 11/2-gal./100-ft.².2. **Deck:** NC**Incline:** 1-1/2**Foam:** — "Ever-Thane Foam", 1-in. minimum.**Surfacing:** — "Ever-Silic HS" applied at a rate of 11/2-gal./100-ft.².3. **Deck:** NC**Incline:** 1**Foam:** — "Ever-Thane Foam", 1-in. minimum.**Base Coat:** — Everroof Group International Corp. "EVER-THANE Base", 1.5-gal/sq.**Top Coat:** — "Ever-Silic HS" applied at a rate of 11/2-gal./100-ft.².**FLUID APPLIED COATING SYSTEMS****Class A**1. **Deck:** C-15/32**Incline:** Unlimited

Barrier Board: — Minimum 1/4-in. thick Georgia-Pacific Gypsum LLC "DensDeck® Roofboard" or "DensDeck Prime® Roofboard" or "DensDeck DuraGuard™ Roofboard" mechanically fastened. The butt joints in the barrier board must be offset a minimum of 6-in. from the butt joints in plywood roof Deck.

Base Coat: — "Ever-Crylic Base Coat" applied at a rate of 1 1/2-gal./100-ft².

Top Coat: — "Ever-Crylic Top Coat" applied at a rate of 1 1/2-gal./100-ft².

2. **Deck:** NC **Incline:** Unlimited

Base Coat: — "Ever-Crylic Base Coat" applied at a rate of 1 1/2-gal./100-ft².

Top Coat: — "Ever-Crylic Top Coat" applied at a rate of 1 1/2-gal./100-ft².

3. **Deck:** C-15/32 **Incline:** Unlimited

Barrier Board: — Minimum 1/4-in. thick Georgia-Pacific Gypsum LLC "DensDeck® Roofboard" or "DensDeck Prime® Roofboard" or "DensDeck DuraGuard™ Roofboard" mechanically fastened. The butt joints in the barrier board must be offset a minimum of 6-in. from the butt joints in plywood roof Deck.

Surfacing: — "Ever-Silic HS" applied at a rate of 1 1/2-gal./100-ft².

4. **Deck:** NC **Incline:** Unlimited

Surfacing: — "Ever-Silic HS" applied at a rate of 1 1/2-gal./100-ft².

5. **Deck:** NC **Incline:** Unlimited

Base Coat: — Everroof Group International Corp. "EVER-THANE Base" applied at a rate of 1 1/2-gal./100-ft².

Top Coat: — "Ever-Silic HS" applied at a rate of 1 1/2-gal./100-ft².

Last Updated on 2017-03-14

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".